

Artificial Intelligence Programming

Intro to Python

Chris Brooks

Department of Computer Science
University of San Francisco

2-2: What is Python?

- Python is:
 - High-level
 - Object-oriented
 - Free, open-source
 - Dynamically typed
 - Has a large collection of utility libraries
 - garbage-collected
 - Mixable - works nicely as a “glue” language
 - Easy to learn/use

2-3: Some uses of Python

- Things that Python is good at:
 - System utilities
 - Python has hooks into standard OS-level services, such as files, processes, pipes, etc.
 - GUIs
 - Python has interfaces to Tk, Qt, and WxPython
 - Embedded integration
 - Python has hooks that allow it to call/be called by C and C++ code, and also COM interfaces.
 - Rapid Interactive Development
 - Like Lisp, Python makes it easy to quickly put together a working program.
 - Scripting
 - Python has utilities for CGI, Database access, HTTP, Sockets, FTP, POP/SMTP, XML parsing, etc.

2-4: Invoking Python Programs

- There are four ways to run a Python program:
 - Interactively
 - From the command line
 - As a script
 - From another program

2-5: Python Implementations

- /usr/bin/python on all unix machines and on OS X
- IDLE and PythonWin on Windows
- MacPython on Macintosh
- Also for Amiga, PalmOS, BeOS, etc.
 - BoaConstructor is an open-source Python IDE

2-6: Python Program Structure

- Programs consist of modules
 - A module corresponds to a source file.
- Modules contain blocks of statements
- Statements create and process objects.

2-7: Basic Python

- Python has a nice set of built-in data types
 - Numbers
 - Strings
 - Lists
 - Dictionaries
 - Files
- Using built-in types makes your code easier to write/maintain, more portable, and more efficient.

2-8: Numbers

- Numbers work like we'd expect.
- There are integers, equivalent to longs in C. (1, -31311, 4000)
- There are *long integers*, which are of unlimited size (31111L, 12345I)
- There are floats, equivalent to doubles in C. 1.23, 3.1e+5
- There are Octal and Hexadecimal representations as in C. (0155, 0x3af5)
- There are complex numbers, as in Lisp, Matlab, etc. (3.0+4j)

2-9: Mathematical Operators

- Python has all the usual mathematical operators
- `+, =, *, /, %`
- `«, »`
- `**` or `pow` for exponentiation
- `abs, rand, |, &`
- This makes Python a very handy desk calculator.
- Operations are coerced to the most specific type.
 - `3 + (4.0 / 2)` will produce a float.

2-10: Strings

- One of Python's strong suits is its ability to work with strings.
- Strings are denoted with double quotes, as in C.
- `s1 + s2` - concatenation
- `s1 * 3` - repetition
- `s1[i]` - indexing, `s1[i:j]` - slicing
- `s1[-1]` - last character
- `"a % parrot" % "dead"` - formatting
- `for char in s1` - iteration

2-11: Strings

- Strings are immutable sequences - to change them, we need to make a copy.
 - Can't do: `s1[3] = 'c'`
 - Must do: `s2 = s1[0:2] + 'c' + s1[3:]`

2-12: Lists

- Python has a flexible and powerful list structure.
- Lists are mutable sequences - can be changed in place.
- Denoted with square brackets. `l1 = [1,2,3,4]`
- Can create nested sublists. `l2 = [1,2, [3,4, [5], 6], 7]`
- `l1 + l2` - concatenation.
- `l1 * 4` - repetition
- `l1[3:5]`, `l1[:3]`, `l1[5:]` - slices
- `append`, `extend`, `sort`, `reverse` built in.
- `Range` - create a list of integers

2-13: Dictionaries

- A Dictionary is a Python hash table (or associative list)
- Unordered collections of arbitrary objects.
- `d1 = {}` - new hashtable `d2 = {'spam' : 2, 'eggs', 3}`
- Can index by key `d2['spam']`
- Can have nested Hashtables
 - `d3 = {'spam' : 1, 'other' : {'eggs' : 2, 'spam' : 3}}`
 - `d3['other']['spam']`
- `has_key`, `keys()`, `values()`, `for k in keys()`
- Typically, you'll insert/delete with:
 - `d3['spam'] = 'delicious!'`
 - `del d3['spam']`

2-14: Tuples

- Tuples are like immutable lists.
- Nice for dealing with enumerated types.
- Can be nested and indexed.
- `t1 = (1,2,3)`, `t2 = (1,2,(3,4,5))`
- Can index, slice, length, just like lists.
 - `t1[3]`, `t1[1:2]`, `t1[-2]`
- Tuples are mostly useful when you want to have a list of a predetermined size/length.
- Also, constant-time access to elements. (fixed memory locations)

2-15: Files

- Since it's a scripting language, Python has a lot of support for file I/O
- Operators are not too different from C.
- `Outfile = file('fname', 'w')` or `infile = file('fname', 'r')`
 - 'r' is default and can be left out
- `S = infile.read()` - read the entire file into the string S.
- `S = infile.read(N)` - read N lines into the string S.
- `S = input.readline()` - read one line
- `S = input.readlines()` - read the whole file into a list of strings.
 - Unless the file is *really* huge, it's fastest to read it all in at once with `read()` or `readlines()`

2-16: Files

- `outfile.write(S)` - write the string `S` into the file.
- `outfile.writelines(L)` - write the list of strings `L` into the file.
- `outfile.close()` (this is also done by the garbage collector)

2-17: Basic Python statements

- Python uses dynamic typing.
 - No need to pre-define variables.
- Variables are instantiated by assigning values to them
 - Referencing a variable before assignment is an error
- You can assign multiple variables simultaneously

```
spam = 4
```

```
eggs = 5
```

```
spam, eggs = eggs, spam
```

```
spam, eggs = 4, 5
```

2-18: Python variables

- Variables must:
 - begin with a letter or underscore
 - contain any number of letters, numbers, or underscores.
- No \$, @, #, etc.
- Case matters.
- Can't use reserved words as variables.

2-19: Printing

- We've already seen the basic print.
 - `print "hello world"`
- To use a formatting string, do:
 - `print "hello %s" % "bob"`
 - `print "%s %s" % ("hello" , "world")`
- To suppress the linefeed, include a ,

2-20: Conditionals

- The general format for an if statement is:

```
if <test1>   :
    <statement1>
    <statement2>
elif: <test2>   :
    <statement3>
else:
    <statementn>
```

- Notice the colons after the conditionals.
- Compound statements consist of the colon, followed by an indented block.

2-21: Conditionals

- Logical tests return 1 for true and 0 for false.
- “True” and “False” are shorthand
- and, or, not are available for compound tests

2-22: Syntax

- Tabs are used to delimit blocks.
- Statements can cross multiple lines if:
 - They're within delimiters
 - You use a backslash

2-23: Iteration

- Python has the familiar while loop.
- One wrinkle: it has an optional else clause to execute if the test is false.
- Additional loop control
 - break
 - Exit the innermost loop without doing an else
 - continue
 - Return to the beginning of the loop
 - pass
 - Do nothing

2-24: For

- For is a generic iterator in Python.
- Lets you loop over any indexable data structure.
 - `for item in [1,2,3,4,5]`
 - `for char in "This is a string"`
 - `for key in dictionary.keys()`
- This provides a uniform (polymorphic) interface to a set of different data structures.

2-25: Functions

- `def` is used to define a function.
- `return` returns a value
- Functions maintain local scope
- Names are resolved locally, then globally, then built-in

2-26: Functions

- Multiple values can be returned in a tuple.
- We can also provide default arguments.
- Functions can be called with keywords.
 - `myfunc(spam=1, eggs=2)`
- `*args` can be used to catch arbitrary argument lists and store them in a tuple.
- `**args` can be used to catch arbitrary argument lists and store them in a dictionary.